# **Understanding Water Relations in a Sloped USGA Putting Green. (C05-frank105003-Oral)**

#### Authors:

- B.E.Leach\* Michigan State University, East Lansing, MI
- K.W.Frank Michigan State University, East Lansing, MI
- J.R.Crum Michigan State University, East Lansing, MI
- T.A.Nikolai Michigan State University, East Lansing, MI

- R.N.Calhoun Michigan State University, East Lansing, MI
- B.R.Leinauer New Mexico State University, Las Cruces, NM

## Abstract:

The United States Golf Association recommendation for putting green construction requires a uniform root zone mix depth of 30 cm over a pea gravel layer. Greens constructed to these specifications have experienced soil moisture problems especially in areas of undulation. Lateral flow of water has lead to excessive soil moisture in low areas, and insufficient soil moisture in elevated areas. A sloping putting green with two different root zone depths was constructed at the Hancock Turfgrass Research Center at Michigan State University. The two root zone mix depths are the standard USGA uniform depth of 30 cm, and a modified depth of 20 and 40 cm at the highest and lowest elevations, respectively. Tipping buckets connected to drain tiles quantified drainage from five locations within each profile. Time domain reflectometry measured volumetric soil moisture at four locations within each profile. Results from 2000 and 2001 indicate that soil moisture, to a depth of 20 cm, is more uniform across a sloping green constructed with a variable depth rootzone.

**Corresponding Author Information:** 

Kevin Frank Michigan State University A175A PSSB Michigan State University East Lansing, MI 48824 phone: 517-432-0729 e-mail: leachbri@msu.edu

### **Presentation Information:**

Presentation Date: Monday, November 11, 2002 Presentation Time: 4:00 pm

### **Keywords:**

USGA putting green, Water relations